



Fletch-Tite Platinum Thinner

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Date of issue: 01/18/2019

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : Fletch-Tite Platinum Thinner

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Arrow fletching adhesives solvent/thinner.

1.3. Details of the supplier of the safety data sheet

Manufacturer:
Bohning Company Ltd.
7361 North Seven Mile Road
Lake City, MI 49651
Tel: 231-229-4247

1.4. Emergency telephone number

Emergency number : HAZMAT +1-800-373-7542 (24 hours)
HAZMAT (International Shipments) +1-484-951-2432 (24 hours)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2 H225 - Highly flammable liquid and vapor
Eye Irrit. 2A H319 - Causes serious eye irritation
Carc. 2 H351 - Suspected of causing cancer
STOT SE 3 H335 - May cause respiratory irritation
STOT SE 3 H336 - May cause drowsiness or dizziness

Full text of H-statements: see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation
H336 - May cause drowsiness or dizziness
H351 - Suspected of causing cancer

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P261 - Avoid breathing fume, gas, mist, spray, vapors
P264 - Wash hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, protective clothing, protective gloves
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P312 - Call a POISON CENTER, a doctor if you feel unwell
P337+P313 - If eye irritation persists: get medical advice/attention
P370+P378 - In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, foam to

Fletch-Tite Platinum Thinner

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container to comply with applicable local, national and international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Methyl ethyl ketone	(CAS No) 78-93-3	60 - 80	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Tetrahydrofuran	(CAS No) 109-99-9	10 - 30	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319 Carc. 2, H351 STOT SE 3, H335
4-methylpentan-2-one, isobutyl methyl ketone	(CAS No) 108-10-1	10 - 30	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation: vapor), H332 Eye Irrit. 2A, H319 STOT SE 3, H335

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). Suspected of causing cancer.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.
First-aid measures after skin contact	: Immediately flush the contact area with plenty of water. Gently wash with plenty of soap and water. Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Repeated exposure may cause skin dryness or cracking. Obtain medical attention.
First-aid measures after eye contact	: Rinse immediately and thoroughly, pulling the eyelids away from eyes (15 minutes minimum). Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause drowsiness or dizziness. May cause respiratory irritation.
Symptoms/injuries after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May cause gastric irritation. Feeling of intoxication. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Sand.
Unsuitable extinguishing media	: Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor. Incomplete combustion releases dangerous carbon monoxide, carbon dioxide and other toxic gases.
-------------	--

Fletch-Tite Platinum Thinner

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

- Explosion hazard : May form explosive peroxides. May form flammable/explosive vapor-air mixture. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Heavier than air, vapors may travel long distances along ground, ignite and flash back to source.
- Reactivity : Stable under use and storage conditions as recommended in section 7. Prolonged storage: may form peroxides.

5.3. Advice for firefighters

- Firefighting instructions : Approach from upwind. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
- Protective equipment for firefighters : Do not enter fire area without proper protective equipment, including respiratory protection.
- Other information : Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. Cool closed containers exposed to fire with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Ensure adequate ventilation. Eliminate all ignition sources if safe to do so. Use special care to avoid static electric charges. No open flames. No smoking. Stop leak if safe to do so. Spilled material may present a slipping hazard. Avoid inhalation of vapor and spray mist. Avoid contact with skin, eyes and clothing.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Do not absorb in saw-dust or other combustible absorbents. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Scoop solid spill into closing containers. Store away from other materials. Use only non-sparking tools. Take precautionary measures against static discharge.
- Other information : Consult the appropriate local waste disposal expert about waste disposal. Ensure all national/local regulations are observed.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Hazardous waste due to potential risk of explosion.
- Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Do not breathe gas, fumes, vapor or spray. Use only outdoors or in a well-ventilated area. Keep away from sources of ignition - No smoking. Avoid contact with skin, eyes and clothing. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.
- Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Contaminated work clothing should not be allowed out of the workplace. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation. Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use spark-/explosion proof appliances and lighting system.

Fletch-Tite Platinum Thinner

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

- Storage conditions : Keep only in the original container in a cool well ventilated place. Keep in fireproof place. Keep container tightly closed. Keep away from heat. Keep out of direct sunlight. Keep away from open flames, hot surfaces and sources of ignition.
- Incompatible materials : Strong oxidizers. Acids. Bases.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methyl ethyl ketone (78-93-3)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	300 ppm
ACGIH	Remark (ACGIH)	URT irr; CNS & PNS impair
OSHA	OSHA PEL (TWA) (mg/m ³)	590 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm

Tetrahydrofuran (109-99-9)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
ACGIH	Remark (ACGIH)	URT irr; CNS impair; kidney dam
OSHA	OSHA PEL (TWA) (mg/m ³)	590 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm

4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	75 ppm
ACGIH	Remark (ACGIH)	URT irr; dizziness; headache
OSHA	OSHA PEL (TWA) (mg/m ³)	410 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

8.2. Exposure controls

- Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation.
- Personal protective equipment : Avoid all unnecessary exposure. Protective goggles. Gloves. Protective clothing. Use personal protective equipment as required.



- Hand protection : Wear protective gloves. Use neoprene or rubber gloves. Impermeable protective nitrile gloves. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
- Eye protection : Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles.
- Skin and body protection : Long sleeved protective clothing. Rubber apron, boots.
- Respiratory protection : An approved organic vapor respirator/supplied air or self-contained breathing apparatus must be used when vapor concentration exceeds applicable exposure limits. Use a properly fitted, air-purifying or air-fed respirator if necessary.
- Environmental exposure controls : Avoid discharge to the environment.
- Other information : Do not eat, drink or smoke during use. Remove contaminated clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : Colorless
- Odor : sweet odor

Fletch-Tite Platinum Thinner

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: < 37.8 °C (<100 °F)
Flash point	: < -9.4 °C (<15 °F)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosive limits	: 1.4 - 11 vol %
Explosive properties	: May form explosive peroxides.
Oxidizing properties	: No data available
Vapor pressure	: 70 - 80 mm Hg
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Density	: > 1
Solubility	: Water: Soluble
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Stable under use and storage conditions as recommended in section 7. Prolonged storage: may form peroxides.

10.2. Chemical stability

Stable under recommended storage conditions. Unstable on exposure to heat. Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Reacts vigorously with strong oxidizers and acids.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks. Overheating.

10.5. Incompatible materials

Strong acids. Strong bases. Oxidizing agent.

10.6. Hazardous decomposition products

May form explosive peroxides. May release flammable gases. Fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure	: Ingestion; Inhalation; Skin and eye contact
Acute toxicity	: Not classified
(Based on available data, the classification criteria are not met)	

Fletch-Tite Platinum Thinner	
ATE US (oral)	5500 mg/kg
Methyl ethyl ketone (78-93-3)	
LD50 oral rat	2483 mg/kg
LD50 dermal rabbit	5000 mg/kg
LC50 inhalation rat (ppm)	11700 ppm/4h
Tetrahydrofuran (109-99-9)	
LD50 oral rat	1650 mg/kg
LC50 inhalation rat (ppm)	21000 ppm (Exposure time: 3 h)

Fletch-Tite Platinum Thinner

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)	
LD50 oral rat	2080 mg/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	8.2 mg/l/4h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)Based on available data, the classification criteria are not met
Carcinogenicity	: Suspected of causing cancer.

Tetrahydrofuran (109-99-9)	
National Toxicology Program (NTP) Status	1 - Evidence of Carcinogenicity

Reproductive toxicity	: Not classified (Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
Potential Adverse human health effects and symptoms	: May cause cancer.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness. May cause respiratory irritation.
Symptoms/injuries after skin contact	: Repeated exposure may cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May cause gastric irritation. Feeling of intoxication. Swallowing the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis.

SECTION 12: Ecological information

12.1. Toxicity

Methyl ethyl ketone (78-93-3)	
LC50 fish 1	3130 - 3320 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	> 520 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Daphnia 2	5091 mg/l (Exposure time: 48 h - Species: Daphnia magna)

Tetrahydrofuran (109-99-9)	
LC50 fish 1	1970 - 2360 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	2700 - 3600 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Methyl ethyl ketone (78-93-3)	
Log Pow	0.29

Tetrahydrofuran (109-99-9)	
BCF fish 1	(will not bioconcentrate)
Log Pow	0.45 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming	: No additional information available
Other information	: Avoid release to the environment.

Fletch-Tite Platinum Thinner

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with applicable local, national and international regulations. Allow volatiles to evaporate. Dispose of solid residue according to applicable regulations. Can be deposited in landfills, sent to an incineration or other appropriate means of disposal provided they meet the requirements of local laws. Ensure all national/local regulations are observed.
Additional information	: Handle empty containers with care because residual vapors are flammable. Hazardous waste due to potential risk of explosion.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1263 Paint related material (including paint thinning, drying, removing, or reducing compound), 3, II
UN-No.(DOT)	: UN1263
Proper Shipping Name (DOT)	: Paint related material including paint thinning, drying, removing, or reducing compound
Transport hazard class(es) (DOT)	: 3 - Class 3 - Flammable liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid



Packing group (DOT)	: II - Medium Danger
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 173
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Special Provisions (49 CFR 172.102)	: 149 B52 IB2 T4 TP1 TP8 TP28
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B
Other information	: No supplementary information available.

TDG

Transport document description	: UN1263 PAINT RELATED MATERIAL (PAINT RELATED MATERIAL), 3, II
UN-No. (TDG)	: UN1263
TDG Proper Shipping Name	: PAINT RELATED MATERIAL
TDG Primary Hazard Classes	: 3 - Class 3 - Flammable Liquids
Packing group	: II - Medium Danger
TDG Special Provisions	: 59 83
Explosive Limit and Limited Quantity Index	: 5
Passenger Carrying Road Vehicle or Passenger Carrying Railway Vehicle Index	: 5

Transport by sea

UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT RELATED MATERIAL

Fletch-Tite Platinum Thinner

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger
MFAG-No	: 127;128

Air transport

UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint related material
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Methyl ethyl ketone (78-93-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
--	---------

Tetrahydrofuran (109-99-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb

4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)

RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb
--	---------

15.2. International regulations

CANADA

Methyl ethyl ketone (78-93-3)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

Tetrahydrofuran (109-99-9)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

4-methylpentan-2-one, isobutyl methyl ketone (108-10-1)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
----------------------	---

EU-Regulations

No additional information available

National regulations

Methyl ethyl ketone (78-93-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

Fletch-Tite Platinum Thinner

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Tetrahydrofuran (109-99-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

15.3. US State regulations

No additional information available

SECTION 16: Other information

Indication of changes : None.
Sources of Key data : Data arise from reference works and literature.
Other information : None.

Full text of H-statements:

Acute Tox. 4 (Inhalation: vapor)	Acute toxicity (inhalation: vapor) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 2	Flammable liquids Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer

SDS US (GHS HazCom 2012)

The conditions of handling, storage, use and disposal of the product covered by this SDS are beyond the control and knowledge of Bohning Archery. Therefore we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. This SDS meets the requirements specified in 29 CFR 1910.1200. Customers are responsible for compliance with local, state, and federal regulations that may be pertinent in the storage, application, and disposal of this product